

WELDING POSITIONER SPECIFICATION SHEET

MODEL	CAPACITY	TABLE DIA	TABLE DIA: WITH EXTN: ARMS, mm	CG mm	ECC mm	TABLE SPEED rpm	TILTING TIME FOR 135 DEG:	LENGTH mm	WIDTH mm	HRIGHT mm
WP-50	50	320		75	50	0.15-2	M			
WP-100	100	320		75	75	0.15-2	M			
WP-200	200	400		75	100	0.1-1.5	M			
WP-250	250	500		100	100	0.1-1.5	60 Sec	1100	820	840
WP-500	500	750		200	150	0.1-1.5	60Sec	1250	850	855
WP-750	750	850		225	175	0.1-1.5	60Sec	1500	1100	1000
WP-1000	1000	1200		250	200	0.07-1	90Sec	1700	1250	1150
WP-1250	1250	1250		265	200	0.07-1	90Sec	1750	1320	1180
WP-1500	1500	1250		270	200	0.07-1	90Sec	1750	1360	1250
WP-2000	2000	1350		275	200	0.07-1	90Sec	1800	1430	1250
WP-2500	2500	1350		285	225	0.04-0.5	90Sec	1840	1500	1350
WP-3000	3000	1400		300	225	0.04-0.5	120Sec	1900	1650	1400
WP-4000	4000	1500		325	225	0.04-0.5	120Sec	2100	1800	1480
WP-5000	5000	1500		340	250	0.02-0.25	120Sec	2200	1900	1600
WP-7500	7500	1800		350	250	0.02-0.25	150Sec	2500	2100	1750
WP-10000	10000	2000		400	250	0.02-0.25	150Sec	2800	2300	1900
WP-15000	15000	2200	3000	500	250	0.02-0.25	150Sec	3500	3000	2200
WP-20000	20000	2500	3500	600	275	0.02-0.25	180Sec	3910	4000	2920
WP-25000	25000	2500	3800	750	275	0.015-0.2	180Sec	4110	4500	3100
WP-30000	30000	2800	4000	900	275	0.015-0.2	180Sec	4510	4500	3250
WP-40000	40000	2800	5000	1000	300	0.015-0.2	240Sec	5100	5000	3350