

**Autorickshaw - 4 Stroke****Specifications**

<b>Engine</b>	4 stroke
<b>Cooling Type</b>	Forced Air Cooled
<b>Displacement</b>	173.52cc
<b>No. of Cylinders</b>	1
<b>Compression Ratio</b>	9.0:1
<b>MaxPower</b>	8.17bhp
<b>Max Power RPM</b>	5000rpm
<b>Max Torque</b>	11.5Nm
<b>Max Torque RPM</b>	4000rpm
<b>Ignition Type</b>	DC
<b>Carburettor</b>	Ucal/Sppaco M10 A
<b>Transmission Type</b>	4 forward and one reverse
<b>Clutch Type</b>	Wet multidisc type
<b>Electrical System</b>	12V DC
<b>Head Light</b>	35/35 W
<b>Horn</b>	12V DC
<b>Chassis Type</b>	Tubelar Type
<b>Front Suspension</b>	Helical coil spring and hydraulic double acting shock absorber
<b>Rear Suspension</b>	Helical coil spring and hydraulic double acting shock absorber
<b>Front Tyre Size</b>	(4.00 - 8).4PR
<b>Rear Tyre Size</b>	(4.00 - 8).4PR
<b>Front Brakes</b>	Drum
<b>Fuel Tank Capacity</b>	8 litres
<b>Reserve Capacity</b>	1 litres
<b>Wheel Base</b>	2000mm
<b>Ground Clearance</b>	200mm
<b>Saddle Height</b>	780mm
<b>Minimum Turning Radius</b>	2.88m
<b>Kerb Weight</b>	295kg
<b>Maximum Payload</b>	335kg
<b>Fuel Efficiency (Ideal)</b>	33kmpl
<b>Fuel Efficiency (Highway)</b>	28 to 32kmpl
<b>Fuel Efficiency (City)</b>	28 to 32kmpl
<b>Max Speed</b>	55kmph

\* (The above model is available in Petrol, CNG and LPG version.)