

TYPE	OUTPUT CAPACITY	POWER REQUIRED	COOLING WATER FEED	BIOLOGICAL PURITY	RH/PH	CONDUCTIVITY	DISTILLATE TEMPERATURE
LQD1	1	220-240 V 2 KW Single Phase	40 Ltr/hr (approx)	PYROGEN FREE	6.9-7	-0.5-0.9X10 <sup>6</sup>	75° +/- 5° C
LQD2	1.5	220-240 V 3 KW Single Phase	60 Ltr/hr (approx)	PYROGEN FREE	6.9-7	-0.5-0.9X10 <sup>6</sup>	75° +/- 5° C
LQD3	2	220-240 V 4 KW Single Phase	60 Ltr/hr (approx)	PYROGEN FREE	6.9-7	-0.5-0.9X10 <sup>6</sup>	75° +/- 5° C
LQD4	2.5	220-240 V 4.5 KW Single Phase	70 Ltr/hr (approx)	PYROGEN FREE	6.9-7	-0.5-0.9X10 <sup>6</sup>	75° +/- 5° C
LQD5	3	220-240 V 5 KW Single Phase	75 Ltr/hr (approx)	PYROGEN FREE	6.9-7	-0.5-0.9X10 <sup>6</sup>	75° +/- 5° C
LQD6	5	220-240 V 8 KW Two Phase	100 Ltr/hr (approx)	PYROGEN FREE	6.9-7	-0.5-0.9X10 <sup>6</sup>	75° +/- 5° C