

## General Purpose laboratory Centrifuges

Technical Data		
Max. Speed	Rpm	5250
Max. Ref	9	3900
Max. capacity	Ml	400
W x D x H	Mm	365 x 415 x 305

Rotor Heads Listing				Reduction Adapters (With Glass Tubes)					
Models	Capacity	Max. Speed	Max. RCF 'g'	RA-501 (1x15 ml)	RA-502 (1x30 ml)	RA-501 (1x wintrob ml)	RA-501 (1x3 ml)	RA-501 (1x5 ml)	RA-501 (1x8 ml)
<b>Swing out Heads (with glass tubes)</b>									
R-81	16x15 ml	4000	2750	x	x	√	√	√	√
R-81A	12x15 ml	4000	2750	x	x	√	√	√	√
R-81B	8x15 ml	4200	3000	x	x	√	√	√	√
R-82	6x50 ml	4000	2800	√	√	x	x	x	x
R-82 A	4x50 ml	4000	2750	√	√	x	x	x	x
<b>Angel Heads (with polypropylene tubes)</b>									
R-83	16 x 15 ml	5250	3600	x	x	√	√	√	√
R-83 A	12 x 15 ml	5250	3600	x	x	√	√	√	√
R-83 B	8 x 15 ml	5250	3600	x	x	√	√	√	√
R-84	6 x 50 ml	5250	3600	√	√	x	x	x	x
R-84 A	4 x 50 ml	5250	3600	√	√	x	x	x	X
<b>Suitable for R -8C DX and R-8C BL</b>									
R-88	4 x 100 ml	5250	3500	x	x	x	x	x	X
R-89	24x15 ml	5250	3900	x	x	x	x	x	x