

Technical Specifications for HYDRAULIC HACKSAW MACHINES

MODEL	M-175	M-200	M-250	M-300	M-350	M-400	M-500	M-600
Cap. of Round Bar	175	200	250	300	350	400	500	600
Cap. of Square Bar	125	150	200	250	275	325	350	425
Stroke	135	135	140	140	140	135	150	150
Strokes per min.(approx)	100-120	100-120	85-100	85-100	85-100	70-85	70-85	70-85
Blade Size	12"-14"	14"-16"	16"-18"	18"-20"	20"-22"	18"-24"	24"-32"	30"-36"
Electric Motor	1 H.R	1 H.R	2 H.R	2 H.R	2 H.R	3 H.R	5 H.R	5 H.R
RPM of Motor	1440	1440	1440	1440	1440	1440	960	960
Length	1000	1000	1150	1250	1300	1500	1650	1750
Width	600	600	625	650	650	675	700	725
Height	800	800	1000	1000	1100	1200	1300	1400
Weight (approx.)	325 Kg.	335 Kg.	450 Kg.	550 Kg.	650 Kg.	750 Kg.	1100 Kg.	1200 Kg.
Weight with Packing	400 Kg.	450 Kg.	550 Kg.	650 Kg.	775 Kg.	900 Kg.	1300 Kg.	1400 Kg.
V-Belts Required	4 Pes.	4 Pes.	4 Pes.	4 Pes.	4 Pes.	5 Pes.	6 Pes.	6 Pes.

Note : As improvements are constantly made in our machines, The specifications are subject to change without notice and are not binding to us.