

FLAMEPROOF, WEATHERPROOF PRODUCTS

Product	Model	Setpoint(s)	Display Digits	RS485 / MODBUS RTU	Supply	Gas groups	Degree of Protection	Mounting
Autotune PID Controller	X96P	5	4+4+3	YES	85~265 V AC 20~35 V DC	I, IIA & IIB	IP 65	Wall
Autotune PID Controller	X48V1	3	4+4	NO	85~265 V AC 20~35 V DC	I, IIA, IIB & IIC	IP 66	2" pipe mounting
Programmable ONOFF Controller	X96A	4	4+4	YES	85~265 V AC 20~35 V DC	I, IIA & IIB	IP 65	Wall
Programmable ONOFF Controller	X48AV1	2	4+4	YES	85~265 V AC	I, IIA, IIB & IIC	IP 66	2" pipe mounting
Programmable ONOFF Controller	TC96	2	4+4	NO	85~265 V AC 20~35 V DC	I, IIA & IIB	IP 65	Wall
Programmable Temperature Indicator	TC48V2	0	4+4	NO	85~265 V AC 24 V DC	I, IIA & IIB	IP 65	Wall/Pipe
Programmable Temperature Controller	TC48V3	2	4+4	NO	85~265 V AC 20~35 V DC	I, IIA, IIB & IIC	IP 66	2" pipe mounting
Multi-channel Scanner	ISOSCAN	16	4.5+4.5+2	YES	85~265 V AC 24 V DC	I, IIA & IIB	IP 55	Wall
Flow Rate Indicator / Totaliser	FLOTO	4	8+6	YES	85~265 V AC 20~35 V DC	I, IIA & IIB	IP 65	Wall
Flow Rate Indicator / Totaliser	FLOTO46	4	6+4	YES	85~265 V AC 20~35 V DC	I, IIA & IIB	IP 65	Wall

Product	Model	Input	Output	Input / Output Isolation	Local Display	Supply	Gas groups	Degree of Protection	Mounting
2-wire Programmable, Isolated Temperature Transmitter	TX3DR	Universal	4~20 mA	YES	4 digit LED	11~32 V DC loop supply	I, IIA, IIB & IIC	IP 66	2" pipe mounting
2-wire Temperature Transmitter	TX1HM	Pt100	4~20 mA / 20~4 mA	NO	LED for Power On status	6.2~32 V DC loop supply	I, IIA & IIB	IP 65	2" pipe mounting
2-wire, Duct Mount RH + Temperature Transmitter	TX6HM	RH+T sensor	2x4~20 mA	NA	-	6~32 V DC	I, IIA, IIB & IIC	IP 66	Duct mount
Loop Powered Indicator	PLD40	4~20 mA	-	NA	4 digit LED display	NA	I, IIA, IIB & IIC	IP 66	2" pipe mounting
Loop Powered Indicator	PLC40	4~20 mA	-	NA	4 digit LCD display	NA	I, IIA, IIB & IIC	IP 66	2" pipe mounting