



At less than 5 lb (2.3 kg), **FreeStyle** by AirSep is the only portable oxygen concentrator tailored specifically for those patients who know no boundaries. Bold and provocative like its name suggests, FreeStyle captures the heart of what it means to live the good life — without limitation. This portable concentrator offers the same weight advantage of a contents-based system, yet provides an unlimited supply of oxygen.

FreeStyle's miniature batteries all fit inconspicuously in an exclusively-designed accompanying AirBelt. This battery belt offers not only function but fashion for those who won't leave home without the assurance of additional hours on FreeStyle. And AirBelt is so lightweight and ergonomically correct that one can easily forget that it's being worn.

FreeStyle is offered as an ensemble consisting of the portable concentrator, shoulder tote, and matching leather AirBelt.

## Specifications

---

**Oxygen Concentration:**\* 1-3 pulse settings equivalent to continuous flow of 90% oxygen

**Dimensions:** 8.6 in. high x 6.1 in. wide x 3.6 in. deep  
(21.8 cm high x 15.5 cm wide x 9.1 cm deep)

**Weight:** 4.4 lb (2 kg), 1.8 lb (.8 kg) optional AirBelt

**Power:** AC Power Supply: 100 – 240 VAC (1.0 amp at 120 VAC)

DC Power Supply 12-16 VDC (6.0 amps at 12 VDC)

**Battery duration:** 3 Lpm - 2 hours; 2 Lpm - 2.5 hours; 1 Lpm - 3.5 hours

Optional AirBelt when combined with the internal battery: 3 Lpm - 5 hours; 2 Lpm - 6 hours;

1 Lpm - 10 hours

**Battery recharge time:** 3.5 hours; optional AirBelt: 3 hours

**Warm-up time:** 2 minutes

**Battery cycle life:** Approximately 300 cycles, then 80% capacity or below

**Audible alarms and visual indicators:** Start-up – audible and visual (GREEN indicator light);  
Pulse flow – visual (GREEN light); Battery condition – battery level (GREEN indicator lights);  
cannula disconnect-audible and visual (RED alarm light); System overdraw – audible and visual  
(RED warning and alarm lights); High and low pressure – audible and visual (RED alarm light);  
Service required: visual (YELLOW alarm light)

**Sound:** Less than 55 decibels

**Temperature range:** Operational temperature: 41°F to 104°F (5°C to 40°C)

Storage temperature: -2°F to 140°F (-20°C to 60°C)

\*Based on an atmospheric pressure of 14.7 psi (101 kPa) at 70°F (21°C)

\*Specifications, including colors, subject to change.