

SPECIFICATIONS	
Display	3½ Digit 7 Segment LED
Range	5 Range 20.00 ppm 200.0 ppm 2000 ppm 20.00 ppt (20,000 ppm) 200.0 ppt (2 lakhs ppm)
Resolution	0.01 ppm
Accuracy	1% FS ± 1 digit
Cell Constant	Adjustable with indication on display.
Temperature Compensation	0 - 50°C
TDS Cell	Platinum Dip Type.
Power	230V AC ± 10% 50Hz
Dimension	60x240x180mm

SPECIFICATIONS	
Indication	4 Digit 7 Segment LED
Range	20.00 ppm / 20.00 µs 200.0 ppm / 200.0 µs 2000 ppm / 2000 µs 20.00 ppt (20,000 ppm) / 20.00 mS 200.0 ppt (2 lakhs ppm) / 200.0 mS Any one of the Range
Resolution	0.01 ppm / µs
Accuracy	1% FS ± 1 digit
Cell Constant	Adjustable with indication on display.
Temperature Compensation	0 - 50°C
Sensor	1/2 inch BSP with 5 mtr cable
Setpoint	1 or 2 relay output are provided
Settings	By front key switches
Power	230V AC ± 10% 50Hz
Dimension	60x240x180mm
Dimension	60x240x180mm