

Flexible Exhaust Connectors Product Range:

Flex ID (mm)	OAL (mm)	Unlined	Braid Lined	Ilok Lined
38.5	101.6	*	*	*
38.5	152.4	*	*	*
38.5	203.2	*	*	*
38.5	230	*	*	*
38.5	251	*	*	*
38.5	280	*	*	*
42.5	101.6	*	*	*
42.5	152.4	*	*	*
42.5	203.2	*	*	*
42.5	230	*	*	*
42.5	251	*	*	*
42.5	280	*	*	*
45.5	101.6	*	*	*
45.5	152.4	*	*	*
45.5	203.2	*	*	*
45.5	230	*	*	*
45.5	262	*	*	*
45.5	280	*	*	*
48.5	105	*	*	*
48.5	152.4	*	*	*
48.5	203.2	*	*	*
48.5	230	*	*	*
48.5	251	*	*	*
48.5	280	*	*	*
51.5	105	*	*	*
51.5	152.4	*	*	*
51.5	203.2	*	*	*
51.5	230	*	*	*
51.5	251	*	*	*
51.5	280	*	*	*
54.5	105	*	*	*
54.5	152.4	*	*	*

Flex ID (mm)	OAL (mm)	Unlined	Braid Lined	Ilok Lined
54.5	203.2	*	*	*
54.5	230	*	*	*
54.5	251	*	*	*
54.5	280	*	*	*
57.5	105	*	*	*
57.5	152.4	*	*	*
57.5	203.2	*	*	*
57.5	230	*	*	*
57.5	251	*	*	*
57.5	280	*	*	*
63.5	105	*	*	*
63.5	152.4	*	*	*
63.5	203.2	*	*	*
63.5	230	*	*	*
63.5	251	*	*	*
63.5	280	*	*	*
76.5	105	*	*	*
76.5	152.4	*	*	*
76.5	203.2	*	*	*
76.5	230	*	*	*
76.5	251	*	*	*
76.5	280	*	*	*
103	105	*	*	*
103	152.4	*	*	*
103	203.2	*	*	*
103	230	*	*	*
103	251	*	*	*
103	280	*	*	*

\* Tolerance will be applicable as per SENIOR standards