

◆ SPECIFICATIONS **INLINE CHECK VALVES**

| Model<br>型式編號 | PT<br>口徑 | A<br>mm | B<br>mm | Flow<br>流量<br>l/min | Max. Pressure<br>最高壓力<br>kgf/cm <sup>2</sup> | Weight<br>重量<br>kg |
|---------------|----------|---------|---------|---------------------|--|--------------------|
| CV-03T        | 3/8"     | 74      | 23      | 40                  | 210  | 0.18               |
| CV-04T        | 1/2"     | 81      | 29      | 60                  |  | 0.33               |
| CV-06T        | 3/4"     | 91      | 35      | 100                 |  | 0.48               |
| CV-08T        | 1"       | 114     | 46      | 150                 |  | 1.10               |
| CV-10T        | 1 1/4"   | 133     | 56      | 200                 |  | 1.98               |
| CV-12T        | 1 1/2"   | 134     | 66      | 280                 |  | 2.78               |
| CV-16T        | 2"       | 153     | 76.5    | 400                 |  | 3.64               |
| CIT-03T       | 3/8"     | 74      | 23      | 40                  | 315  | 0.18               |
| CIT-04T       | 1/2"     | 81      | 29      | 60                  |  | 0.33               |
| CIT-06T       | 3/4"     | 91      | 35      | 100                 |  | 0.48               |
| CIT-08T       | 1"       | 114     | 46      | 150                 |  | 1.10               |
| CIT-10T       | 1 1/4"   | 133     | 56      | 200                 |  | 1.98               |
| CIT-12T       | 1 1/2"   | 134     | 66      | 280                 |  | 2.78               |
| CIT-16T       | 2"       | 153     | 76.5    | 400                 |  | 3.64               |

◆ SPECIFICATIONS **SUBPLATE AND LINE MOUNTED CHECK VALVES**

| Model Number<br>型式號碼 | Maximum Pressure<br>最大壓力 bar | Connecting PT<br>通用管徑 | Maximum Flow<br>最大流量 lpm | Weight 重量 Kg  |                |
|----------------------|------------------------------|-----------------------|--------------------------|---------------|----------------|
|                      |                              |                       |                          | 40 Type       | 50 Type        |
| CV-03G-*.*           | 250 (3625 psi)               | 3/8"                  | 60 (1.85 gpm)            | 1.9 (4.2 lbs) | 2 (4.4 lbs)    |
| CV-06G-*.*           |                              | 3/4"                  | 125 (33.02 gpm)          | 4.2 (9.3 lbs) | 3.32 (7.3 lbs) |
| CV-10G-*.*           |                              | 1 1/4"                | 250 (66.04 gpm)          | 7.7 (17 lbs)  | 6 (13.2 lbs)   |

◆ SPECIFICATIONS **MODULAR CHECK VALVES**

| Model Number<br>型式號碼 | Maximum Pressure<br>最大壓力 bar | Connecting PT<br>通用管徑 | Maximum Flow<br>最大流量 lpm | Weight<br>重量 Kg |
|----------------------|------------------------------|-----------------------|--------------------------|-----------------|
| MPC-03-A, B          | 250 (3625 psi)               | 3/8"                  | 80 (21.13 gpm)           | 2.6 (5.7 lbs)   |
| MPC-03-W             |                              |                       |                          | 2.8 (6.2 lbs)   |
| MPC-03-AD, BD        | 315 (4500 psi)               | 3/8"                  | 120 (31.70 gpm)          | 3.6 (7.9 lbs)   |
| MPC-03-WD            |                              |                       |                          |                 |