

**Technical data Series 40 axial piston variable displacement pumps**

	Dimension	Frame sizes			
		025	035	044	046
Displacement	cm <sup>3</sup> [in <sup>3</sup> ]	25 [1.5]	35 [2.1]	44 [2.7]	46 [2.8]
Minimum speed	min <sup>-1</sup> (rpm)	500	500	500	500
Rated speed	min <sup>-1</sup> (rpm)	4000	3600	3300	4000
Maximum speed	min <sup>-1</sup> (rpm)	5000	4500	4100	4100

**Technical data Series 42 axial piston variable pumps**

	Dimension	Frame Sizes		
		028	041	051
Displacement	cm <sup>3</sup> [in <sup>3</sup> ]	28 [1.7]	41 [2.5]	51 [3.1]
Minimum speed	min <sup>-1</sup> (rpm)	500	500	500
Rated speed	min <sup>-1</sup> (rpm)	3400	3200	3200
Maximum speed	min <sup>-1</sup> (rpm)	3750	3600	3400

**Technical data Series 90 axial piston variable displacement pumps**

	Dimension	Frame Sizes						
		042	055	075	100	130	180	250
Displacement	cm <sup>3</sup> [in <sup>3</sup> ]	42 [2.6]	55 [3.4]	75 [4.6]	100 [6.1]	130 [7.9]	180 [11.0]	250 [15.3]
Minimum speed	min <sup>-1</sup> (rpm)	500	500	500	500	500	500	500
Rated speed	min <sup>-1</sup> (rpm)	4200	3900	3600	3300	3100	2600	2300
Maximum speed	min <sup>-1</sup> (rpm)	4600	4250	3950	3650	3400	2850	2500