

HORIZONTAL DRIVE WHEELS

	CARICO MAX RUOTA MAX WHEEL LOAD (kg)	MOTORI ELETTRICI ELECTRIC MOTORS (W)	TENSIONE VOLTAGE (V)	DIAM. RUOTA WHEEL SIZE (mm)
i- D10 - M70	400÷600	250÷500	12÷48	205
0	2200÷1100*	1000÷2500	24÷48	300/330
240	1000÷650*	450-1200	12÷48	250
250	1000÷650*	600÷1200	24÷48	250
300	1350÷750*	600÷1200	24÷48	300
270	1300	750÷1500	24÷48	270
260/300 Mot. D.151	1500	1000÷2500	24÷48	300
260/350 Mot. D.151	2000	1000÷2500	24÷48	350
260/350 Mot. D.191	2000	2500÷3500	24÷80	350
260/406 Mot. D.191	2300	2500÷3500	24÷80	406
350	2600	2500÷3500	24÷80	350
415	4000	5000÷7000	48÷80	406

VERTICAL DRIVE WHEELS

	CARICO MAX RUOTA MAX WHEEL LOAD (kg)	MOTORI ELETTRICI ELECTRIC MOTORS (W)	TENSIONE VOLTAGE (V)	DIAM. RUOTA WHEEL SIZE (mm)
.125ECO	1400÷430*	600÷1200	12÷48	230
.151ECO	1400÷430*	1000÷2500	12÷48	230
.151	1800÷850*	1000÷2500	12÷48	260
.191	1800÷850*	2500÷3500	24÷80	260
.350 Mot. Ø191	3000	2500÷3500	24÷80	350
.350 Mot. Ø244	3000	5000÷7000	48÷80	350
.425 Mot. Ø191	3100	2500÷3500	24÷80	406
.425 Mot. Ø244	3100	5000÷7000	48÷80	406