

Gear motor product range

Model	Mounting flange	Displacement range cm ³ /rev [in ³ /rev]	Max rated pressure bar [psi]	Features
SKU1 SKM1	European 4-bolt and SAE A-A 2-bolt	0.26 - 12 [0.2 - 0.7]	250 [3625]	Unidirectional (SKU1) and bi-rotational (SKM1) - SAE A-A 9T splined, 1:8 & 1:5 taper, 12 and keyed 12.7 mm - O-ring boss ports, Euro 4-bolt ports - European/metric options
SNU2 SNM2	European 4-bolt and SAE A 2-bolt flanges	8.4 - 25.2 [0.5 - 1.5]	250 [3625]	Unidirectional (SNU2) and bi-rotational (SNM2) - SAE A 9T spline, 1:8 and 1:5 taper, 15 and 15.875 mm keyed - O-ring boss ports, European 4-bolt ports - Integral valves (special rear cover) - Fan drive versions with integral control and relief valves - Radial case drain option - European/metric options
SNU3 SNM3	European 4-bolt flange SAE B 2-bolt	22.1 - 63.4 [1.4 - 3.9]	250 [3625]	Unidirectional (SNU3) and bi-rotational (SNM3) - SAE B 13T spline, 1:8 and 1:5 taper, 22; 22.225 and 24mm keyed - O-ring boss ports, SAE B and Euro 4-bolt ports, split flange ports - Motor mounted fan drive versions control and relief valves - European/metric options
MYCP	SAE A 2-bolt flange	9.5 - 31.8 [0.6 - 1.9]	240 [3481]	Unidirectional and bi-rotational - SAE A 11T spline and 9T spline - 0.75in. straight key shaft - O-ring boss ports - A/C checks available