

Gear pump product range

Model	Mounting flange	Displacement range cm ³ /rev [in ³ /rev]	Max rated pressure bar [psi]	Features
TFP 50	Special 2-bolt	0.25 - 1.2 [0.015 - 0.07]	180 [2610]	Special power-pack versions available Bi-rotational pump version available
SNP 1	European 4-bolt	1.2 - 7.7 [0.1 - 0.5]	250 [3625]	Available with internal drain relief valve Special power-pack versions available
SKP 1	SAE A-A 2-bolt	1.2 - 12 [0.1 - 0.7]	250 [3625]	Available with internal drain relief valve Special power-pack version available
YCC (Multiple Pumps)	SAE A 2-bolt	9.5 - 14 [0.6 - 0.9]	172 [2495]	Compact multiple pump configuration
SNP 2 SKP 2	European 4-bolt etc. SAE A 2-bolt	3.9 - 25.2 [0.2 - 1.5]	250 [3625]	Available with priority flow divider, flow control valve, internal/external drain relief valves
D Series	SAE A 2-bolt SAE B 2-bolt	7.0 - 41.0 [0.4 - 2.5]	241 [4000]	Cast-iron range Single and compact multiple units
SNP 3	European 4-bolt etc. SAE B 2-bolt	22.1 - 88.2 [1.4 - 5.4]	250 [3625]	Available with integral relief valve, priority flow divider
35 CI	SAE B 2 & 4-bolt	26.0 - 70.0 [1.6 - 4.3]	275 [2989]	Special variants with integral charge-pressure priority valves available
CP 180	SAE B 2-bolt	32.9 - 97.5 [2.0 - 6.0]	250 [3625]	Cast iron body, aluminum flange cover. Single and tandem and multiple with priority flow divider
CP222	SAE C 2 & 4-bolt	64.8 - 162.0 [4.0 - 9.9]	207 [3002]	Cast iron body, aluminum flange and cover