


# LIFT VALVES

## ◆ SPECIFICATIONS 規格



Model Number 型式號碼	Maximum Pressure 最大壓力 bar	Maximum Flow 最大流量 lpm	Weight 重量 Kg
LVSH-02G	315 (4500 psi)	35 (9.25 gpm)	2.4 (5.3 lbs)
Fluid Type 液體型式		ISO VG 32, 46, 68	
Viscosity 黏性 cSt		10~400 (59~1854 SSU)	
Operating Temperature 操作溫度 °C		-15~70 (-5~158°F)	
Contamination Level 污染標準		$\beta_{10} \geq 75$ , Under NAS Class 12, 25 $\mu$	
Surface Treatment 表面處理		Zinc Phosphate Compound 鋅磷鹽化合物	

## ◆ SPECIFICATIONS 規格

Model Number 型式號碼	Maximum Pressure 最大壓力 bar	Maximum Flow 最大流量 lpm	Weight 重量 Kg
LVSH-03G	315 (4500 psi)	50 (13.21 gpm)	2.4 (5.3 lbs)
Fluid Type 液體型式		ISO VG 32, 46, 68	
Viscosity 黏性 cSt		10~400 (59~1854 SSU)	
Operating Temperature 操作溫度 °C		-15~70 (-5~158°F)	
Contamination Level 污染標準		$\beta_{10} \geq 75$ , Under NAS Class 12, 25 $\mu$	
Surface Treatment 表面處理		Zinc Phosphate Compound 鋅磷鹽化合物	

## ◆ SPECIFICATIONS 規格

Model Number 型式號碼	Maximum Pressure 最大壓力 Mpa	Maximum tank line back pressure 最大容許背壓 Mpa	Maximum tank frequencies of operation 最高切換頻率	Maximum Flow 最大流量 lpm	Weight 重量 Kg	
					AC	DC
LKT-03	21 (210 kgf/cm <sup>2</sup> )	0.07 (0.7 kgf/cm <sup>2</sup> )	60 Cycles/min	30 (7.92 gpm)	1.7 (3.7 lbs)	1.7 (3.7 lbs)
Fluid Type 液體型式				ISO VG 32, 46, 68		
Viscosity 黏性 cSt				10~400 (59~1854 SSU)		
Operating Temperature 操作溫度 °C				-15~70 (-5~158°F)		
Contamination Level 污染標準				$\beta_{10} \geq 75$ , Under NAS Class 12, 25 $\mu$		

